

# Primer N

## Polyurethane lacquer / Primer

### PRODUCT DESCRIPTION

**Primer N** contains MDI based isocyanates and solvents.

### AREA OF USE

**Primer N** is a non-pigmented floor lacquer for binding and impregnation of dry concrete and mortar surfaces. Concrete surfaces must be dry when applying otherwise both the penetration and adhesion will be poor.

Light grey concrete which appears to be dry can generally be treated.

**Primer N** will react with free water to give pores in the impregnation.

**Primer N** takes 3 hours to dry and is completely cured after 3 to 4 days.

The drying time is somewhat dependent upon the substrate, plus material consumption and temperature.

The result is a hard lacquer with high strength and good adhesion to concrete.

### DIRECTIONS FOR USE

Apply **Primer N** using a brush, or squeegee. Material consumption approx. 0.1 kg/m<sup>2</sup> per coat.

Consumption is dependent on the porosity of the concrete surface.

A squeegee is a suitable application tool for flat surfaces e.g. filled surfaces which need to be strengthened.

### SAFETY INSTRUCTIONS

For health, safety and environmental information, see separate safety data sheet at [www.mapei.com](http://www.mapei.com)

### WARNING

*Although the technical details and recommendations contained in this product report correspond to the best of our knowledge and experience, all the above information must, in every case be taken as merely indicative and subject to confirmation after long-term practical applications: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application; in every case, the user alone, is fully responsible for any consequences deriving from the use of the product.*

*All deliveries from Mapei AS are made in accordance with the sale- and delivery conditions applicable at the time, and these conditions are taken to be accepted on placement of an order.*

TECHNICAL SPECIFICATIONS	
Packaging:	<b>Primer N</b> is supplied in 20 kg metal cans. Stored frost free in unopened packaging, product properties remain unchanged. Approx. 50 cP
Storage:	
Viscosity +20°C:	

### Manufacturer:

Mapei AS

Vallsetvegen 6, 2120 Sagstua, Norway

Tlf: +47 62 97 20 00 Fax: +47 62 97 20 99

post@mapei.no

www.mapei.com

